




Hangzhou Binthen Intelligence Technology Co.,Ltd

ADD: ROOM301, 3RD FLOOR BULIDING 1 , JINXING
INDUSTRIAL ZONE YUHANG DISTRICT ZHEJIANG, CHINA
WEBSITE: www,binthen.com EMAIL: info@binthen.com



MOTORIZED CURTAIN TRACK SYSTEM

PRODUCT MAUNAL





About Us Company Profile

Committed to popularize the electric curtain that each family can afford motorized curtain

Hangzhou BINTHEN Intelligence Technology Co., Ltd is located in hanghzhou ,which ranks the top of the Chinese modern technology industry, focus on designing creating marking and selling intelligent shading products. The company has strong power to create , good at making breakthrough. They inherit the "artisan" spirit, be strict to quality, be careful to manufacture, pursue perfection, devote themselves to make the products with high quality, be professional, be reliable and be Cost-effective.

Main products of the company are: intelligent curtain track, smart home product, tubular motor, curtain motor, blind/shutter motor controller system and accessories, and so on.Perfect creating system insures good quality of the products.

Here are complete product inspection process ,professional laboratory equipment and Product aging test. Monitor each production processes, design precisely, create elaborately, test carefully, make sure every product has been checked 100%, present the most reliable product to final users.

The company sets professional assembly line to produce all kinds of motors, every assembly line has its test process, so that insure each goods' stability. The excellent warehouse management promises us improve turnover and Shipping efficiency, ensure delivery products within the order time.

The products through the authority of quality system certification and environmental management quality system certification,3 years quality assurance, high-quality after-sales service provides timely and efficient follow-up protection of products.

Domestic sales and distribution center of Hangzhou Binthen

| Haethi | Haethi | Haethi | Shenyang | Shenyang | Shenzhen | Shenzhen













Binthen distribution center













CONTENTS



Motorized curtain track solutions	01-03
Motorized curtain kit specifications	02
Motorized curtain track system	03
Motorized curtain kit	04-11
Common kit solution	05
Smart kit solution	06-11
TUYA smart kit	06
Ali smart kit	07
JD smart kit	08
Coolkit smart kit	09
Zhuoju smart kit	10
Broadlink smart kit	11
Allgo smart kit	12
Motorized lift curtain system	13-15
Motorized Rome pole system	16
Accessories —Curtain motor	17-21
BCM100D series	18
Battery box	19

BCM300D series	20	
BCM700D series	21	
Accessories—remote controller	22-25	
Optional accessories	26-27	
Motor applications solutions	28-35	
3 wires motor solution	29	
4 wires motor solution	30	
5 wires motor solution	31-32	
RS485 motor solution	33	
Smart control solution	34-35	
Installation dimension requiremen	nts	36-4
Open-closing curtain installation	37	
Motorized Rome pole installation	38-39	
Motorized lift curtain installation	40	



MOTORIZED CURTAIN TRACK SOLUTIONS




01


Motorized curtain track kit specifications


		Track Track	Track	Adjustable Track					
NO.	Size	Length (mm)	Connector (mm)	Track Length (mm)		Track Connector (mm)		Suitable Size(M) (Wall To Wall)	
		1000	100	500	200	100	200	100	, in the second of the second
1	2.2m	1	1	1	2	1	1	1	Under2.2m
2	3.2m	2	2	1	2	1	1	1	2.2m-3.2m
3	4.2m	3	3	1	2	1	1	1	3.2m-4.2m
4	5.2m	4	4	1	2	1	1	1	4.2m-5.2m
5	6.2m	5	5	1	2	1	1	1	5.2m-6.2m
6	7 . 2m	6	6	1	2	1	1	1	6.2m-7.2m
7	8.2m	7	7	1	2	1	1	1	7.2m-8.2m

Note: 1.500mm,200mm,100mm tracks are adjustable track, 200mm,100mm are track connectors 2.Optional accessories:Side mounting brack, 90°angle

Spliced track system







Achieve home smart control of curtain

Manual start

Pull curtain about 10cm by hand, curtain will open or close automatically.

Manual operation if power cut

When there is no power , you can open or close by hand easily.

Middle position set

set a middle stop location at the middle of open and close position to make the better light.

Multiple controls

Choose remote control ,switch, or smart remote control accordingly.

Track length free spiced

DIY design, get any length needed.

Automatically set the memory running point

After powering off,the motor will set running point of open and close again when power on.

MOTORIZED CURTAIN TRACK KIT





MOTORIZED CURTAIN TRACK KIT

Standardization of non-standard products

Original production assembly, standardized combination



Parts in kit motor/ tracks /remote controller /accessories

Quick assemble track Motors and tracks produced by original factory Initial design original match

PATENTED PRODUCT Set sale quick and fast

Rated power 40W Rated torque 1.2 Nm

Maximum load 50kg Rated voltage AC100v~240v

Warranty 3 years Protection level IP20



Manual start

Pull curtain about 10cm by hand, curtain will open or close automatically.

Multiple controls

Choose remote control, switch, or smart remote control accordingly.

Manual operation if power cut

When there is no power, you can open or close by hand

Automatically set the memory running point

After powering off, the motor will set running point of open and close again when power on.

Middle position set

set a middle stop location at the middle of open and close position to make the better light.

Track length free spiced

DIY design, get any length needed.

MOTORIZED CURTAIN TRACK SMART KIT







Features:

Suitable for BCM700D-TUYA motor; Log in by TUYA account,

Suitable for domestic and foreign markets; The router needs to be connected to the network; Support a variety of intelligent speakers control;

Rated power 40W Rated torque 1.2 Nm Maximum load 50kg Rated voltage AC100v~240v Protection level IP20 Warranty 3 years

Control method: 433MHz WIFI SMART SPEAKERS



Manual start

Pull curtain about 10cm by hand, curtain will open or close automatically.

Multiple controls

Choose remote control, switch, or smart remote control accordingly.

Manual operation if power cut

When there is no power. you can open or close by hand easily.

Middle position set

Set a middle stop location at the middle of open and close position to make the better light.

Automatically set the memory running point

After powering off, the motor will set running point of open and close again when power on.

Track length free spiced

DIY design, get any length



MOTORIZED CURTAIN TRACK ALI SMART KIT









Features:

External WiFi module, suitable for BCM300DS motors; Log in by Ali cloud , Taobao account, suitable for demestic market remote control; The router needs to be connected to the network controlled by Tmall speaker;

Rated power 40W Rated torque 1.2 Nm

Maximum load 50kg Rated voltage AC100v~240v

Warranty 3 years Protection level IP20

Control method: 433MHz WIFI SMART SPEAKERS















Support external Ali smart wifi module

MOTORIZED CURTAIN TRACK JD WEILIAN SMART KIT

京东微联





Connect to JDweilian smart control system download JD smart APP to add curtain device

Features:

External WiFi module ,suitable for BCM300DS motors; Log in by JD account, suitable for demestic market remote control; The router needs to be connected to the network controlled by JD speaker;

Rated torque 1.2 Nm

Maximum load 50kg Rated voltage AC100v~240v

Warranty 3 years Protection level IP20

Control method: 433MHz WIFI SMART SPEAKERS













Support external JD wifi module

Manual start

Pull curtain about 10cm by hand, curtain will open or close automatically.

Multiple controls

Choose remote control, switch, or smart remote control accordingly.

Manual operation if power cut

When there is no power you can open or close by hand

Middle position set

set a middle stop location at the middle of open and close position to make the better light.

Automatically set the memory running point

After powering off, the motor will set running point of open and close again when power on.

Track length free spiced

DIY design, get any length needed.

Manual start

Pull curtain about 10cm by hand, curtain will open or close automatically.

Multiple controls

Choose remote control, switch, or smart remote control accordingly.

Manual operation if power cut

When there is no power you can open or close by hand easily.

Middle position set

set a middle stop location at the middle of open and close position to make the better light.

Automatically set the memory running point

After powering off, the motor will set running point of open and close again when power on.

Track length free spiced

DIY design, get any length needed.



MOTORIZED CURTAIN TRACK COOLKIT SMART KIT





Connect to e-support smart control system, download e-support smart APP to add curtain device

Features:

Suitable for BCM500D-KZ series motor; Log in by e-support account ,suitable in domestic market;

Remote control, The router needs to be connected to the network; Controlled by many smart speakers;

Rated power 40W Rated torque 1.2 Nm

Maximum load 50kg Rated voltage AC100v~240v

Warranty 3 years Protection level IP20

Control method: 433MHz WIFI SMART SPEAKERS















MOTORIZED CURTAIN TRACK JOYRILL SMART KIT





Features:

Suitable for BCM500D-ZJ series motor; Log in by homepro account ,suitable in domestic market, remote control; Connected to gateway, controlled by many widely used smart speakers, such as Baidu xiaodu, Tmall smart speakers, and so on;

Rated	power	40W

Rated torque 1.2 Nm

Warranty 3 years

Maximum load 50kg Rated voltage AC100v~240v Protection level IP20

Control method: 433MHz both-way communication

SMART SPEAKERS















BCM500D-ZJ

Manual start

Pull curtain about 10cm by hand, curtain will open or close automatically.

Multiple controls

Choose remote control, switch, or smart remote control accordingly.

Manual operation if power cut

When there is no power you can open or close by hand

After powering off,the motor will

set running point of open and

close again when power on.

running point

Automatically set the memory Track length free spiced

DIY design, get any length needed.

Middle position set

to make the better light.

set a middle stop location at the

middle of open and close position

Manual start

Pull curtain about 10cm by hand, curtain will open or close automatically.

Multiple controls

Choose remote control, switch, or smart remote control accordingly.

Manual operation if power cut

When there is no power you can open or close by hand easily.

Middle position set

set a middle stop location at the middle of open and close position to make the better light.

Automatically set the memory running point

After powering off,the motor will set running point of open and close again when power on.

Track length free spiced

DIY design, get any length needed.

09



MOTORIZED CURTAIN TRACK BROADLINK SMART KIT



Connect to ZHIHUIXING smart control system download e-support smart APP to add curtain device

Features:

Suitable for BCM700D-GB series motor; Log in by ZHIHUIXING account ,suitable in domestic market remote control; The router needs to be connected to the network controlled by some widely used smart speakers;

Rated power 40W	Rated torque 1.2 Nm
Maximum load 50kg	Rated voltage AC100v~240v
Warranty 3 years	Protection level IP20

Control method: 433MHz WIFI SMART SPEAKERS















MOTORIZED CURTAIN TRACK ALLGO SMART KIT



Based on Allgo protocl

Features:

Suitable for BCM500D-LW series motor; Adopt Allgo protocol ,suitable for products belongs to Allgo alliances, can remote control; The router needs to be connected to the network controlled by some widely used smart speakers;

Rated power 40W	Rated torque 1.2 Nm		
Maximum load 50kg	Rated voltage AC100v~240v		
Warranty 3 years	Protection level IP20		

Control method: 433MHz both-way communication









BCM500D-LW

Manual start

Pull curtain about 10cm by hand, curtain will open or close automatically.

Multiple controls

Choose remote control, switch, or smart remote control accordingly.

Manual operation if power cut

When there is no power you can open or close by hand easily.

Middle position set

set a middle stop location at the middle of open and close position to make the better light.

Automatically set the memory running point

After powering off,the motor will set running point of open and close again when power on.

11

Track length free spiced

DIY design, get any length needed.

Manual start

Pull curtain about 10cm by hand, curtain will open or close automatically.

Multiple controls

Choose remote control, switch, or smart remote control accordingly.

Manual operation if power cut

When there is no power you can open or close by hand easily.

Middle position set

set a middle stop location at the middle of open and close position to make the better light.

Automatically set the memory running point

After powering off,the motor will set running point of open and close again when power on.

Track length free spiced

DIY design, get any length needed.



MOTORIZED LIFT CURTAIN

Standardized assemble shceme Adjustable size Systematic design

Easy to assemble





Adopt easy disassemly design, easy to install and remove the motor Be used for straight curtain tracks

The motor has been patented on clutch, and the stroke can be set automatically, can be control manually and by remote Radio receiver can be make inside or outside of motor, can be connect with other control systems, easy to make smart control Minimal noise, minimal vibrate

High quality full coating track, move by belt with stainless steel wires



Assemble



remote





silent





running





operation



control



load



fast

4 1160mm×201mm×70mm

technology

PATENTED TELESCOPIC STRUCTURE SYSTEM




Sizes of telescopic structure lift system suitable length Assemble size 3m 2.078m-3.018m 3.078m-4.964m 4.090m-6.910m

PATENTED

Remarks: Out of these sizes can be customized

Motorized Lift Curtain packaging



PATENTED TELESCOPIC STRUCTURE SYSTEM Examples of assemble length 7m set: adjustable extent 4.090m-6.910m 5m set: adjustable extent 3.078m-4.964m 3m set: adjustable extent 2.078m-3.018m ☐ Example:3m ☐ Example:2.5m □ Example:2.2m





LIFT SYSTEM

Adopt high quality tubular motor to supply power

Easy to control,stable operation


The motor has been patented on clutch

The stroke can be set automatically,can be control manually and by remote

Radio receiver can be make inside or outside, can be connect with

other control systems,easy to make smart control






Descend




ACCESSORIES

Easy to install
High strength belt,strong and durable
Easy to adjust



Terminal for tubular motor Easy to connect wires



MOTORIZED ROME POLE SYSTEM























remote

Super Silent

Smooth Running


Radio Control

Manual Operation

Large Load

pad

Fast Te



Manual start

Pull curtain about 10cm by hand, curtain will open or close automatically.

Manual operation if power cut

When there is no power , you can open or close by hand easily.

Middle position set

Set a middle stop location at the middle of open and close position to make the better light.

|Multiple controls


Choose remote control ,switch, or smart remote control accordingly.

Automatically set the memory running point

After powering off,the motor will set running point of open and close again when power on.

Track length free spiced

DIY design, get any length needed.



ACCESSORIZE / CURTAIN MOTOR

17



















ssembled High



BCM100DB

Low power consumption DC motor Possess battery power

Lithium cell power

Battery capacity: 2200MAH Battery voltage: 12v Maximum output current: 4A Slow charge input: 5v/16.8v Fast charge input: 2A



BCM100DC

247 270. 5

Four wires motor DC power input Strong current switch control Can be use in projects

and hotels

BCM100D5X

Five wires motor Possess remote control and strong current switch control

BCM100D-RS485

Support RS-485 control
RS-485 Motor
Can be connect into smart system
Multi-motors synchronization
control
Save cost with high quality



Battery box for motorized curtain system


Easy to install, high capacity, support long working time

Easy to solve no power plug nearby the window No need to rewiring Conveniente and fast Long battery life with fast charge

Power supplied by battery ,connect motor and battery by DC-DC cable. very convenient.Remove the battery to charge,it can be charging more than 300 times.

Battery capacity:2200MAH Battery voltage:12V Maximum output current:4A slow charge input:5V/2A fast charge input:16.8V/1.4A







USB slow charging port, connect with MICRO (mobile phone charger port) DC005-3.5*1.35 Fast charging port, connect with adapter. DC005-5,5*2,1 output port. Connect motor by DC cable. Fully charge indicator lamp Charging indicator lamp

Battery box instruction

1. There are 3 ports (2 of them are charging ports) and 2 indicators; 2.DC005-3.5*1.35 is fast charging port, charging by adapter mostly, charging time is about 2.5h;

3.MICRO is slow charging port, Charging by 5V/1.5A (or over) phone charger, charging time is about 8h;

4.Output port is DC005-5,5*2.1, connect DC-DC cable to motor to

5.Red light means charging, Green light means charging over.

Wiring method

Connect motor with battery box by DC-DC cable, two sides DC cable are the same. One side plug cable into DC output port and the other side plug into discharging output port of battery box. The DC -DC cable is 1.5M, easy to remove and charging.

Charging reminder

If users find the motor make "didi" noise, it means lack of power, should charge it.

















remote

control

operation


BCM300D **DC Curtain Motor**



Intellgent speaker control Smart kit

Join smart system

Product Size /mm





BCM300DB

Low power consumption DC motor Possess battery power

Lithium cell power

Battery capacity: 2200MAH Battery voltage: 12v Maximum output current: 4A Slow charge input: 5v/16.8v Fast charge input: 2A



BCM300DC

Four wires motor DC power input Strong current switch control Can be use in projects

and hotels

BCM300D5X

Five wires motor Possess remote control and strong current switch control

BCM300D-RS485

Support RS-485 control RS-485 Motor

Can be connect into smart system Multi-motors synchronization control Save cost with high quality

BCM300D

Smart type Wifi motor Join tuya APP system Support varieties of popular speakers control Customize scene setting Timing operation



















remote

running

control

operation

BCM700D **DC Curtain Motor**

Technical Parameters

Rated Torque	1. 2 NM			
Rated Voltage	AC100-240V			
Rated Consumption	40W			
Max Load	50 KG			
Radio Distance	>50M			
IP	IP20			
Warranty	3 years			




Smart kit

Intellgent speaker control

Join smart system

产品尺寸/mm





BCM700D-TY



Smart type Wifi motor Join tuya APP system Support varieties of popular speakers control Customize scene setting Timing operation

BCM700D-GB BroadLink

Smart type Wifi motor Join broadlink-zhihuixing APP system Support varieties of popular speakers control Customize scene setting Timing operation

ACCESSORIZE / REMOTE CONTROLLER





INTELLIGENT CONTROL SYSTEM

Low power consumption, stable signal Easy using for all families

Multiple terminal devices can be control in same time Easy to set up,multi-operations by one touch





Wall design remote



BE102

Wall Design Double Channel

Power Supply: 3V (CR2032) Output frequency: 433.92MHz

Output Power: 10mw

Working Temperature: -10 C ~50 C

Distance: >50 m

Wall assembling



Remote controller



BE201

Single Channel

Power Supply: 2*1.5V (AAA) Output frequency: 433.92MHz
Output Power: 10mw

Working Temperature: -10 °C ~50 °C

Distance: >50 m

Wall bracket for option



BE206

Six Channel

Power Supply: 2*1.5V (AAA) Output frequency: 433.92MHz Output Power: 10mw Working Temperature: -10 C~50 C Distance: >50 m

Wall bracket for option



BE202

Two Channel

Power Supply: 2*1.5V (AAA) Output frequency: 433.92MHz Output Power: 10mw Working Temperature: -10 C ~50 C

Distance: >50 m

Wall bracket for option

OPTIONAL ACCESSORIES



26



BE216LT

16 channels LCD timing emitter

Power Supply: 2*1.5V (AAA) Output frequency: 433.92MHz Output Power: 10mw

Working Temperature: -10 ℃~50 ℃

Distance: >50 m

Wall bracket for option



25

BE216L

16 channels LCD emitter

Power Supply: 2*1.5V (AAA) Output frequency: 433.92MHz Output Power: 10mw

Working Temperature: -10 C ~50 C

Distance: >50 m

Wall bracket for option



SIDE MOUNTING BRACKET



Single track side mounting bracket




CORNER CONNECTOR

90° corner connector



135° corner connector





MOTOR APPLICATIONS SOLUTIONS




3 WIRES MOTOR SOLUTIONS

Functions

3 wires motor as basic motor can be control by remote, weak current dry contact switch and so on, applicable to multi-scene.

Change the control mode



Change the control mode for weak current dry contact switch:


Hold close and stop buttons in same time for 3 seconds, the motor will vibrate once, control mode change to next mode.

Mode1:applicable to double interlock switch(Factory default settings)


Mode2:applicable to double reset switch

Mode3:applicable to single reset switch

Wiring diagram for weak current double button switch



Wiring diagram for weak current double button switch



4 WIRES MOTOR SOLUTIONS


Functions

4 wires motor not possess RF control, not support remote control, only use strong current switch. Applicable to hotel, smart home and decoration project etc.

Wiring diagram and functions



Notice: switch type is strong current double interlock switch, 4 wires motor can't connect with weak current switch



Wiring diagram




5 WIRES MOTOR SOLUTIONS

Functions

5 wires motor possess RF control, support remote control, strong current dry contact switch, strong current switch, plug-in card power supply and so on. Applicable to hotel, smart home and decoration project etc.

Change the control mode



Change the control mode for weak current dry contact switch:

Hold close and stop buttons in same time for 3 seconds, the motor will vibrate once, control mode change to next mode.


Mode1:applicable to double interlock switch(Factory default settings)

Mode2:applicable to double reset switch

Mode3:applicable to single reset switch

mode4:applicable to plug-in card power supply

Wiring diagram for plug-in card power supply




The control mode should be mode 4 when use plug-in card power supply, take off card curtain will open, put in card curtain will close.

If you need to use switch and plug-in card in same time, you can only connect weak current double interlock button with Lan port, can't use strong current switch


Wiring diagram for weak current double button switch




Wiring diagram for weak current single button switch



Wiring diagram for strong current double button switch



Wiring diagram for strong current single button switch




RS-485 MOTOR SOLUTIONS

Functions

RS-485 motor possess RF control, support remote control and RS485 bus control. Applicable to smart home and hotel project etc.

Wiring diagram for RS485





Other control modes


RS485 motor can be control by remotes and weak current dry contact switch, more details please check 3 wires motor solutions.

MOTORIZED CURTAIN ZIGBEE SMART CONTROL SOLUTION

ZIGBEE protocol connect

For most motorized curtain in the market can t connect to living samrt home control system directly ,and the poor integration ,we adopt ZIG BEE technology ,set up a motorized curtain control system wireless network by doordinator ,routing nodes and terminal nodes ,gateway PAD .Through the online detecting light sensor to detect the current light intensity, according to current light value and the system time to control the corresponding node in curtain motor in networlk automatically , so as to realize the intelligent light-control of the curtain.

BINTHEN smart control motor ,has stably information transmission with the ZIGBEE system,can satisfy the demands of smart home project designs



34



MOTORIZED CURTAIN SMART CONTROL SOLUTION

Z-wave protocol connect control



Z-WAVE Working frequency

						Malisia /MHz	
8	368.4	908.4/ 916	868.4	919.8/ 921.4	922.5/ 923.9/ 926.3	868.1	869.0



Z-WAVE protocol smart control

Z-WAVE ALLIANCE now contains more than 160 famous corporations ,almost cover all over the world ,any country ,any district ,the members in the origanization are the manufacturers who already has their porducts in smart home field, BINTHEN curtain motor has finished the connections with Z-WAVE protocol,can realize smart control easily


WIFI intelligent control

Features:

Set up a network through WIFI and router ,realize the local/remote control , enjoy the smart home anywhere
Adopt the intelligent wireless match code ,control the appliances freely
Support many kinds of scene modes ,timing modes , get different control experiences
You can add or delete appliances at the terminal control side ,set different modes




INSTALLATION DIMENSION REQUIREMENTS






DIMENSION REQUIRE FOR INSTALL THE MOTORIZED CURTAIN TRACK SYSTEM

Single track





Notice:

The motor should be install nearby the power port


Notice:

The roof should be strong enough for hold the full weight of tracks motor and curtain fabrics

Double track



Distance between track cap and side wall need to keep more than 10mm




Double tracks (double curtains)


37

DIMENSION REQUIRE FOR INSTALL THE MOTORIZED ROME POLE SYSTEM

Full window




The window on the middle of the wall






The window on the one side of wall



F=300-A-48.5(mm) H=L+300-105-B+20+18 (mm) Length of each belt for center open (two belts): H+60(mm)

For example, use the standard tails, the far edge of window to the side wall has 2000mm, pole length is 2100mm, A=130mm,B=185mm, the center opening beside the side wall, the uncover part is 300mm, the distance between the bracket near to center opening and the wall is 120mm, the distance between the bracket near to subsidiary opening and the window edge is 120mm





G=300-B-18. 5 (mm) H=L+300-A+20+18 (mm) Length of the belt for single-side open (one belt): 2 × (H+60) +25 (mm)

For example, use the standard tails, the far edge of window to the side wall has 2000mm, pole length is 2105mm, A=130mm,B=185mm, the subsidiary opening beside the side wall, the uncover part is 300mm, the distance between the bracket near to center opening and the window edge is 100mm, teh distance between the bracket near to subsidiary opening and the side wall is 70mm

DIMENSION REQUIRE FOR INSTALL THE LIFT SYSTEM







Notice:

1.The distance between walls and the two ends of device should be more than 50mm.

2.The distance between the device and the back wall should be more than 75mm, the width and depth of curtain box should be more than 250mm.